




NUMINOS® DL M

Indoor LED recessed ceiling light black/chrome 3000 K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1550 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1003867
Number of different light outlets	1
IP Code	IP20/IP44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1550 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black/chrome
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.242 kg
Gross weight	0.28 kg

Light Source

791822	
--------	---

Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29 W 500 mA
1004064	LED driver , 21-29.5 W 500/600/700 mA
1006459	LED bridge driver , 42 W, 500 mA for NUMINOS®, including radio interface for RF module, DALI
1004054	LED driver , 20 W 500 mA PHASE
1006139	Numinos® S Reducing ring , round 160/100 mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100 mm white
1006142	Numinos® S Reducing ring , square 160/100 mm white
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1006141	Numinos® S Reducing ring , square 160/100 mm black

Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm