




## NUMINOS® S 3Ph.

**PHASE, 3~ Spotlight, cylindrical, 3000 K, 8 Watt, trailing edge, 60°, matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1050 lm and an impressive efficiency of 131.25 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1004084           |
| Number of different light outlets | 1                 |
| IP Code                           | IP20              |
| Assembly details                  | Ceiling, Wall     |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Primary nominal voltage           | 220-240AC50/60 Hz |
| Secondary power / voltage         | 200               |
| Safety class                      | I                 |
| Wattage                           | 8 W               |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Number of luminaires at LS B16A   | 128               |
| Number of luminaires at LS C16A   | 128               |
| Level of inrush current           | 10 A              |
| Duration of inrush current        | 50 µs             |
| Lumen                             | 1050 lm           |
| Colour temperature                | 3000 Kelvin       |
| Beam angle                        | 60 °              |
| Color                             | matt black        |
| CRI                               | 90                |
| Service life                      | 50000 h           |

## Light Source

|         |                                                                                   |                       |          |
|---------|-----------------------------------------------------------------------------------|-----------------------|----------|
| 1411580 |  | <b>Risk Group</b>     | 1        |
|         |                                                                                   | <b>Length</b>         | 16.2 cm  |
|         |                                                                                   | <b>Height</b>         | 14 cm    |
|         |                                                                                   | <b>Diameter</b>       | 6.5 cm   |
|         |                                                                                   | <b>Net weight</b>     | 0.517 kg |
|         |                                                                                   | <b>Gross weight</b>   | 0.815 kg |
|         |                                                                                   | <b>BIG WHITE Page</b> | 629      |