




NUMINOS® S PD

PHASE, Pendant light, pendant length 250 cm, 3000 K, 8 Watt, 24°, trailing edge, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® S PD, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 1050 lm and an impressive efficiency of 131.25 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004154
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	128
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	200
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	128
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	matt black
CRI	90

Light Source

1411580		Service life	50000 h
		Risk Group	1
		Height	16.2 cm
		Diameter	6.5 cm
		Pendant length	250 cm
		Net weight	0.7 kg
		Gross weight	0.893 kg
		BIG WHITE Page	233