


## NUMINOS® S PD

**PHASE, Pendant light, pendant length 250 cm, 3000 K, 8 Watt, 36°, trailing edge, matt white / matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® S PD, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 1050 lm and an impressive efficiency of 131.25 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                       |
|-----------------------------------|-----------------------|
| Item no.                          | 1004159               |
| Number of different light outlets | 1                     |
| IP Code                           | IP20                  |
| Assembly                          | Surface               |
| Dimmable                          | Yes                   |
| Dimming technology                | trailing edge         |
| Number of through-wires           | 128                   |
| Primary nominal voltage           | 220-240AC50/60 Hz     |
| Secondary power / voltage         | 200                   |
| Safety class                      | I                     |
| Wattage                           | 8 W                   |
| Minimum ambient temperature       | -20 °C                |
| Maximum ambient temperature       | 45 °C                 |
| Number of luminaires at LS B16A   | 128                   |
| Number of luminaires at LS C16A   | 128                   |
| Level of inrush current           | 10 A                  |
| Duration of inrush current        | 50 µs                 |
| Lumen                             | 1050 lm               |
| Colour temperature                | 3000 Kelvin           |
| Beam angle                        | 36 °                  |
| Color                             | matt white/matt black |
| CRI                               | 90                    |

## Light Source

|         |                                                                                   |                       |
|---------|-----------------------------------------------------------------------------------|-----------------------|
| 1411580 |  |                       |
|         |                                                                                   | <b>Service life</b>   |
|         |                                                                                   | 50000 h               |
|         |                                                                                   | <b>Risk Group</b>     |
|         |                                                                                   | 1                     |
|         |                                                                                   | <b>Height</b>         |
|         |                                                                                   | 16.2 cm               |
|         |                                                                                   | <b>Diameter</b>       |
|         |                                                                                   | 6.5 cm                |
|         |                                                                                   | <b>Pendant length</b> |
|         |                                                                                   | 250 cm                |
|         |                                                                                   | <b>Net weight</b>     |
|         |                                                                                   | 0.7 kg                |
|         |                                                                                   | <b>Gross weight</b>   |
|         |                                                                                   | 0.893 kg              |
|         |                                                                                   | <b>BIG WHITE Page</b> |
|         |                                                                                   | 233                   |