




## NUMINOS® M 3Ph.

**PHASE, 3~ Spotlight, cylindrical, 4000 K, 14 Watt, trailing edge, 24°, matt white / matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1950 lm and an impressive efficiency of 139.29 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                       |
|-----------------------------------|-----------------------|
| Item no.                          | 1004190               |
| Number of different light outlets | 1                     |
| IP Code                           | IP20                  |
| Assembly details                  | Ceiling               |
| Dimmable                          | Yes                   |
| Dimming technology                | trailing edge         |
| Primary nominal voltage           | 220-240AC50/60 Hz     |
| Secondary power / voltage         | 350                   |
| Safety class                      | I                     |
| Wattage                           | 14 W                  |
| Minimum ambient temperature       | -20 °C                |
| Maximum ambient temperature       | 45 °C                 |
| Number of luminaires at LS B16A   | 78                    |
| Number of luminaires at LS C16A   | 78                    |
| Level of inrush current           | 10 A                  |
| Duration of inrush current        | 50 µs                 |
| Lumen                             | 1950 lm               |
| Colour temperature                | 4000 Kelvin           |
| Beam angle                        | 24 °                  |
| Color                             | matt white/matt black |
| CRI                               | 90                    |
| Service life                      | 50000 h               |

## Light Source

|         |                                                                                   |                       |          |
|---------|-----------------------------------------------------------------------------------|-----------------------|----------|
| 1411588 |  | <b>Risk Group</b>     | 1        |
|         |                                                                                   | <b>Length</b>         | 18.5 cm  |
|         |                                                                                   | <b>Height</b>         | 15.5 cm  |
|         |                                                                                   | <b>Diameter</b>       | 8.5 cm   |
|         |                                                                                   | <b>Net weight</b>     | 0.797 kg |
|         |                                                                                   | <b>Gross weight</b>   | 1.087 kg |
|         |                                                                                   | <b>BIG WHITE Page</b> | 631      |