




NUMINOS® M PD

PHASE, Pendant light, pendant length 250 cm, 2700 K, 14 Watt, 36°, trailing edge, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® PD, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 1750 lm and an impressive efficiency of 125 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004243
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	78
Number of luminaires at LS C16A	78
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	1750 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	matt black
CRI	90

Light Source

1411536		
		Service life
		50000 h
		Risk Group
		1
		Height
		18.5 cm
		Diameter
		8.5 cm
		Pendant length
		250 cm
		Net weight
		0.979 kg
		Gross weight
		1.198 kg
		BIG WHITE Page
		235