




NUMINOS® L CL

PHASE, Surface-mounted ceiling light, 2700 K, 20 Watt, trailing edge, 60°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 2300 lm and an impressive efficiency of 115 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004320
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	78
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	500
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	78
Number of luminaires at LS C16A	78
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	2300 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	matt white/matt black

Light Source

1411536		CRI	90
		Service life	50000 h
		Risk Group	1
		Height	21.3 cm
		Diameter	10 cm
		Net weight	1.018 kg
		Gross weight	1.299 kg
		BIG WHITE Page	187