




## NUMINOS® L CL

**PHASE, Surface-mounted ceiling light, 4000 K, 20 Watt, trailing edge, 60°, matt white / matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 2600 lm and an impressive efficiency of 130 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                       |
|-----------------------------------|-----------------------|
| Item no.                          | 1004336               |
| Number of different light outlets | 1                     |
| IP Code                           | IP20                  |
| Assembly                          | Surface               |
| Assembly details                  | Ceiling               |
| Dimmable                          | Yes                   |
| Dimming technology                | trailing edge         |
| Number of through-wires           | 78                    |
| Primary nominal voltage           | 220-240AC50/60 Hz     |
| Secondary power / voltage         | 500                   |
| Safety class                      | I                     |
| Wattage                           | 20 W                  |
| Minimum ambient temperature       | -20 °C                |
| Maximum ambient temperature       | 45 °C                 |
| Number of luminaires at LS B16A   | 78                    |
| Number of luminaires at LS C16A   | 78                    |
| Level of inrush current           | 10 A                  |
| Duration of inrush current        | 50 µs                 |
| Lumen                             | 2600 lm               |
| Colour temperature                | 4000 Kelvin           |
| Beam angle                        | 60 °                  |
| Color                             | matt white/matt black |

## Light Source

|         |                                                                                   |                |          |
|---------|-----------------------------------------------------------------------------------|----------------|----------|
| 1411588 |  | CRI            | 90       |
|         |                                                                                   | Service life   | 50000 h  |
|         |                                                                                   | Risk Group     | 1        |
|         |                                                                                   | Height         | 21.3 cm  |
|         |                                                                                   | Diameter       | 10 cm    |
|         |                                                                                   | Net weight     | 1.018 kg |
|         |                                                                                   | Gross weight   | 1.299 kg |
|         |                                                                                   | BIG WHITE Page | 187      |