




## NUMINOS® L PD

**PHASE, Pendant light, pendant length 250 cm, 4000 K, 20 Watt, 60°, trailing edge, matt black**

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® PD, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 2600 lm and an impressive efficiency of 130 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1004356           |
| Number of different light outlets | 1                 |
| IP Code                           | IP20              |
| Assembly                          | Surface           |
| Dimmable                          | Yes               |
| Dimming technology                | trailing edge     |
| Number of through-wires           | 78                |
| Primary nominal voltage           | 220-240AC50/60 Hz |
| Secondary power / voltage         | 500               |
| Safety class                      | I                 |
| Wattage                           | 20 W              |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Number of luminaires at LS B16A   | 78                |
| Number of luminaires at LS C16A   | 78                |
| Level of inrush current           | 10 A              |
| Duration of inrush current        | 50 µs             |
| Lumen                             | 2600 lm           |
| Colour temperature                | 4000 Kelvin       |
| Beam angle                        | 60 °              |
| Color                             | matt black        |
| CRI                               | 90                |

## Light Source

|         |                                                                                   |                       |
|---------|-----------------------------------------------------------------------------------|-----------------------|
| 1411588 |  |                       |
|         |                                                                                   | <b>Service life</b>   |
|         |                                                                                   | 50000 h               |
|         |                                                                                   | <b>Risk Group</b>     |
|         |                                                                                   | 1                     |
|         |                                                                                   | <b>Height</b>         |
|         |                                                                                   | 21.3 cm               |
|         |                                                                                   | <b>Diameter</b>       |
|         |                                                                                   | 10 cm                 |
|         |                                                                                   | <b>Pendant length</b> |
|         |                                                                                   | 250 cm                |
|         |                                                                                   | <b>Net weight</b>     |
|         |                                                                                   | 1.278 kg              |
|         |                                                                                   | <b>Gross weight</b>   |
|         |                                                                                   | 1.516 kg              |
|         |                                                                                   | <b>BIG WHITE Page</b> |
|         |                                                                                   | 237                   |