




NUMINOS® S 3Ph.

DALI, 3~ Spotlight, cylindrical, 3000 K, 7.8 Watt, DALI, 24°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® S 3Ph., DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1050 lm and an impressive efficiency of 134.62 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004374
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	DALI, Touch
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	200
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	166
Number of luminaires at LS C16A	187
Level of inrush current	2.425 A
Duration of inrush current	202 µs
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	matt white/matt black
CRI	90
Service life	50000 h

Light Source

1411580		Risk Group	1
		Length	16.2 cm
		Height	14.5 cm
		Diameter	6.5 cm
		Net weight	0.579 kg
		Gross weight	0.897 kg
		BIG WHITE Page	629