




## NUMINOS® S CW

DALI, Surface-mounted ceiling light, 3000 K, 7.8 Watt, DALI, 24°, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 1050 lm and an impressive efficiency of 134.62 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1004394           |
| Number of different light outlets | 1                 |
| IP Code                           | IP20              |
| Assembly                          | Surface           |
| Assembly details                  | Ceiling           |
| Dimmable                          | Yes               |
| Dimming technology                | DALI,Touch        |
| Number of through-wires           | 166               |
| Primary nominal voltage           | 200-240AC50/60 Hz |
| Secondary power / voltage         | 200               |
| Safety class                      | I                 |
| Wattage                           | 8 W               |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 50 °C             |
| Number of luminaires at LS B16A   | 166               |
| Number of luminaires at LS C16A   | 187               |
| Level of inrush current           | 2.425 A           |
| Duration of inrush current        | 202 µs            |
| Lumen                             | 1050 lm           |
| Colour temperature                | 3000 Kelvin       |
| Beam angle                        | 24 °              |
| Color                             | matt black        |

## Light Source

|         |                                                                                   |                |          |
|---------|-----------------------------------------------------------------------------------|----------------|----------|
| 1411580 |  | CRI            | 90       |
|         |                                                                                   | Service life   | 50000 h  |
|         |                                                                                   | Risk Group     | 1        |
|         |                                                                                   | Length         | 16.2 cm  |
|         |                                                                                   | Height         | 14.5 cm  |
|         |                                                                                   | Diameter       | 6.5 cm   |
|         |                                                                                   | Net weight     | 0.615 kg |
|         |                                                                                   | Gross weight   | 0.943 kg |
|         |                                                                                   | BIG WHITE Page | 337      |