




NUMINOS® S CL

DALI, Surface-mounted ceiling light, 2700 K, 7.8 Watt,
DALI, 36°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® S CL, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 950 lm and an impressive efficiency of 121.79 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004415
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	166
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	200
Safety class	I
Wattage	7.8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	166
Number of luminaires at LS C16A	187
Level of inrush current	2.425 A
Duration of inrush current	202 µs
Lumen	950 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	matt white/matt black

Light Source

1411525		CRI	90
		Service life	50000 h
		Risk Group	1
		Height	16.2 cm
		Diameter	6.5 cm
		Net weight	0.476 kg
		Gross weight	0.716 kg
		BIG WHITE Page	183