


NUMINOS® M 3Ph.

DALI, 3~ Spotlight, cylindrical, 3000 K, 13 Watt, DALI, 24°, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 1800 lm and an impressive efficiency of 138.46 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1004466 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI,Touch |
| Primary nominal voltage | 200-240AC50/60 Hz |
| Secondary power / voltage | 350 |
| Safety class | I |
| Wattage | 14 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 50 °C |
| Number of luminaires at LS B16A | 94 |
| Number of luminaires at LS C16A | 94 |
| Level of inrush current | 2.75 A |
| Duration of inrush current | 190 µs |
| Lumen | 1800 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | matt black |
| CRI | 90 |
| Service life | 50000 h |

Light Source

| | |
|---------|---|
| 1411586 |  |
|---------|---|

| | |
|-----------------------|----------|
| Risk Group | 1 |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.833 kg |
| Gross weight | 1.147 kg |
| BIG WHITE Page | 631 |