


NUMINOS® L PD

DALI, Pendant light, pendant length 250 cm, 4000 K, 19 Watt, 60°, DALI, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® PD, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 2600 lm and an impressive efficiency of 136.84 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1004648
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	94
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	500
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	94
Number of luminaires at LS C16A	94
Level of inrush current	2.75 A
Duration of inrush current	190 µs
Lumen	2600 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	matt white/matt black
CRI	90

Light Source

1411588		
		Service life
		50000 h
		Risk Group
		1
		Height
		21.3 cm
		Diameter
		10 cm
		Pendant length
		250 cm
		Net weight
		1.474 kg
		Gross weight
		1.733 kg
		BIG WHITE Page
		237