




OCULUS UP/DOWN WL

Indoor LED wall-mounted light black 2000-3000 K

With a high colour rendering index (CRI >90) and the option of dim-to-warm dimming for an especially warm light (2000-3000 K), every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting.



TECHNICAL DATA

Item no.	1004670
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	15 W
Ambient temperature	85 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	26
Number of luminaires at LS C16A	42
Level of inrush current	15 A
Duration of inrush current	10 µs
Lumen	22-555 lm
Colour temperature	2000-3000 Kelvin

Light Source

916398		Beam angle	100 °
		Color	black
		CRI	90
		Service life	25000 h
		Risk Group	1
		Height	11 cm
		Depth	12.5 cm
		Diameter	9 cm
		Net weight	0.867 kg
		Gross weight	1.049 kg
		BIG WHITE Page	385