




PANEL TRACK round 200 mm

1-phase spot, white, 18 W 3000 K

Modern and space-saving at the same time, PANEL provides efficient basic lighting. A pleasant, homogeneous and glare-free light is produced by the 1-phase system light LED with 1,800 lumen and 3,000 Kelvin. Made of polycarbonate (PC) and steel, it is also extremely sustainable with an LED lifespan of 50,000 hours. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.	1004936
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance	0.2 Joule
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	450 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	20 µs
Lumen	1800 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
Service life	50000 h
Risk Group	1
Length	23.1 cm
Width	20 cm
Height	11.05 cm

Light Source

916407	
--------	---

Net weight	0.46 kg
Gross weight	0.632 kg
BIG WHITE Page	589