


## WORKLIGHT

**black free-standing lamp. 79W 4000K 80°**


As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office free-standing light for VDU workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and, of course,  $UGR \leq 19$ . Equipped with a motion sensor, the built-in daylight control and the possibility of dimming, it meets all the requirements of today's office lighting. The WORKLIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable including plug. This light contains integrated LED light bulbs.



## TECHNICAL DATA

|                                   |                   |
|-----------------------------------|-------------------|
| Item no.                          | 1005390           |
| Number of different light outlets | 2                 |
| IP Code                           | IP 20             |
| Impact resistance class           | IK 02             |
| Impact resistance                 | 0.2 Joule         |
| Assembly                          | Mobile            |
| Dimmable                          | Yes               |
| Dimming technology                | Touch             |
| Primary nominal voltage           | 200-240V ~50/60Hz |
| Secondary power / voltage         | 2000 mA           |
| Safety class                      | I                 |
| Wattage                           | 79 W              |
| Minimum ambient temperature       | -20 °C            |
| Maximum ambient temperature       | 45 °C             |
| Number of luminaires at LS B16A   | 28                |
| Number of luminaires at LS C16A   | 28                |
| Level of inrush current           | 6.24 A            |
| Duration of inrush current        | 194 µs            |
| Stroboscopic effect (SVM)         | 0                 |
| Lumen                             | 7600 lm           |
| Colour temperature                | 4000 Kelvin       |
| Beam angle                        | 80 °              |

### Light Source

|        |   |
|--------|---|
| 916336 |  |
|        |   |

|                       |           |
|-----------------------|-----------|
| <b>Color</b>          | black     |
| <b>CRI</b>            | 80        |
| <b>UGR ≤</b>          | 19        |
| <b>LXXBXX data</b>    | L80B10    |
| <b>Service life</b>   | 50000 h   |
| <b>Risk Group</b>     | 0         |
| <b>Length</b>         | 69.2 cm   |
| <b>Width</b>          | 31 cm     |
| <b>Height</b>         | 195 cm    |
| <b>Net weight</b>     | 14.307 kg |
| <b>Gross weight</b>   | 17.288 kg |
| <b>BIG WHITE Page</b> | 445       |