



NUMINOS® MOVE XS

white recessed ceiling light, 3000K $40^{\circ}\,$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1005584
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	2
Height	5.5 cm
	-



Light Source

798303	Å F	
Accessories		
1006136	Numinos® XS Reducing ring , round 160/70mm white	
1006135	Numinos® XS Reducing ring , round 160/70mm black	
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	
1005614	NUMINOS® XS , frosted diffuser	
1006454	RF module Casambi for LED bridge driver , single colour	
1006199	RF module Zigbee for DALI LED bridge driver , single colour	
1005612	NUMINOS® XS , diffuser	
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005615	NUMINOS® XS , black diffuser	
1006137	Numinos® XS Reducing ring , square 160/70mm black	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1006138	Numinos® XS Reducing ring , square 160/70mm white	
1005613	NUMINOS® XS , transparent diffuser	
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI	

Diameter	8 cm
Net weight	0.135 kg
Gross weight	0.165 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	86