




NUMINOS® XL PD

DALI, Pendant light, pendant length 250 cm, 4000 K, 27 Watt, 36°, DALI, matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® PD, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Pendelleuchte The luminaire impresses with a luminous flux of 3900 lm and an impressive efficiency of 144.44 lm/W. Their colour temperature of 4000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1005790
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	58
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	700
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	58
Number of luminaires at LS C16A	58
Level of inrush current	2.825 A
Duration of inrush current	188 µs
Lumen	3900 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	matt black
CRI	90

Light Source

1411588		
		Service life
		50000 h
		Risk Group
		1
		Height
		25.8 cm
		Diameter
		12 cm
		Pendant length
		250 cm
		Net weight
		1.952 kg
		Gross weight
		2.262 kg
		BIG WHITE Page
		239