



NUMINOS® XL 3Ph.

DALI, 3~ Spotlight, cylindrical, 2700 K, 27 Watt, DALI, 36°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® 3Ph., DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The 3~ Spot The luminaire impresses with a luminous flux of 3550 lm and an impressive efficiency of 131.48 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1005799
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	200-240AC50/60 Hz
Secondary power / voltage	700
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	58
Number of luminaires at LS C16A	58
Level of inrush current	2.825 A
Duration of inrush current	188 µs
Lumen	3550 lm
Colour temperature	2700 Kelvin
Beam angle	36 °
Color	matt white/matt black
CRI	90
Service life	50000 h

Light Source

1411536		Risk Group	1
		Length	20.8 cm
		Height	20 cm
		Diameter	12 cm
		Net weight	1.549 kg
		Gross weight	1.993 kg
		BIG WHITE Page	635