



## NUMINOS® GIMBLE S

black / chrome recessed ceiling light, 2700K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® GIMBLE S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005869                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 250 mA                  |
| Safety class                      | III                     |
| Wattage                           | 8.6 W                   |
| Lumen                             | 690 lm                  |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 7 cm                    |
| Diameter                          | 10 cm                   |
| Net weight                        | 0.2 kg                  |
| Gross weight                      | 0.24 kg                 |
| Shape of cut-out                  | round                   |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791819 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                                                            |
|---------|--------------------------------------------------------------------------------------------|
| 1006458 | LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004789 | NUMINOS® S , diffuser Wabe                                                                 |
| 1004067 | LED driver , 15W 250mA DALI                                                                |
| 1004788 | NUMINOS® S , diffuser Frosted                                                              |
| 1004787 | NUMINOS® S , diffuser Prisma                                                               |
| 1004786 | NUMINOS® S , diffuser Ellipse                                                              |
| 1006139 | Numinos® S Reducing ring , round 160/100mm black                                           |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1004058 | LED driver , 6.5-10W 250mA                                                                 |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006140 | Numinos® S Reducing ring , round 160/100mm white                                           |
| 1006142 | Numinos® S Reducing ring , square 160/100mm white                                          |
| 1004055 | LED driver , 6.5-10W 250mA PHASE                                                           |
| 1006141 | Numinos® S Reducing ring , square 160/100mm black                                          |

|                       |      |
|-----------------------|------|
| Installation depth    | 7 cm |
| Installation diameter | 9 cm |
| BIG WHITE Page        | 88   |