



## NUMINOS® GIMBLE M

black / white recessed ceiling light, 4000K 40°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® GIMBLE M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005961                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 500 mA                  |
| Safety class                      | III                     |
| Wattage                           | 17.5 W                  |
| Lumen                             | 1750 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 9.5 cm                  |
| Diameter                          | 13.5 cm                 |
| Net weight                        | 0.45 kg                 |
| Gross weight                      | 0.55 kg                 |
| Shape of cut-out                  | round                   |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791825 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                                                            |
|---------|--------------------------------------------------------------------------------------------|
| 1004792 | NUMINOS® M , diffuser Frosted                                                              |
| 1004069 | LED driver , 29W 500mA                                                                     |
| 1004064 | LED driver , 21-29.5W 500/600/700mA                                                        |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black                                           |
| 1004054 | LED driver , 20W 500mA PHASE                                                               |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white                                          |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white                                           |
| 1004793 | NUMINOS® M , diffuser Wabe                                                                 |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black                                          |
| 1004790 | NUMINOS® M , diffuser Ellipse                                                              |
| 1004791 | NUMINOS® M , diffuser Prisma                                                               |

|                       |        |
|-----------------------|--------|
| Installation depth    | 9.5 cm |
| Installation diameter | 12 cm  |
| BIG WHITE Page        | 89     |