




NUMINOS® GIMBLE M

black recessed ceiling light, 4000 K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® GIMBLE M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1005963
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Secondary power / voltage	500 mA
Safety class	III
Wattage	17.5 W
Temperature at glass (light emission)	109 °C
Lumen	1600 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	matt black/black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	9.5 cm
Diameter	13.5 cm
Net weight	0.448 kg
Gross weight	0.561 kg
Shape of cut-out	round
Installation depth	9.5 cm
Installation diameter	12 cm

Light Source

791825	
--------	---

Accessories

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29 W 500 mA
1004064	LED driver , 21-29.5 W 500/600/700 mA
1006459	LED bridge driver , 42 W, 500 mA for NUMINOS®, including radio interface for RF module, DALI
1006143	Numinos® M Reducing ring , round 240/120 mm black
1004054	LED driver , 20 W 500 mA PHASE
1006146	Numinos® M Reducing ring , square 240/120 mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120 mm white
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006145	Numinos® M Reducing ring , square 240/120 mm black
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma