



NUMINOS® XL CL

PHASE, Surface-mounted ceiling light, 3000 K, 28 Watt, trailing edge, 24°, matt white / matt black

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, PHASE LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 3550 lm and an impressive efficiency of 126.79 lm/W. Their colour temperature of 3000 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.



TECHNICAL DATA

Item no.	1006092
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	54
Primary nominal voltage	220-240AC50/60 Hz
Secondary power / voltage	700
Safety class	I
Wattage	27 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	54
Number of luminaires at LS C16A	54
Level of inrush current	10 A
Duration of inrush current	50 µs
Lumen	3550 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	matt white/matt black

Light Source

1411586		CRI	90
		Service life	50000 h
		Risk Group	1
		Length	25.8 cm
		Height	20 cm
		Diameter	12 cm
		Net weight	1.676 kg
		Gross weight	2.121 kg
		BIG WHITE Page	343