



NUMINOS® ZOOM M PHASE

black 3-phase spot, 20W 2700K 15-60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1006108
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	680-1650 lm
Colour temperature	2700 Kelvin
Beam angle	15 °
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	40000 h
Risk Group	1

Light Source

791800		Length	19 cm
		Height	16.5 cm
		Diameter	8.5 cm
		Net weight	0.989 kg
		Gross weight	1.302 kg
		BIG WHITE Page	115