




MANA BASE WL PHASE

**Wall-mounted light anthracite round 15 W 800/820 lm
2700/3000 K CRI 90 Dimmable**

The MANA BASE WL PHASE wall light is dimmable and designed with a high-performance LED, which allows configuration of the colour temperature before installation (2700/3000 K). Thanks to its IP65 protection class rating, this aluminium and polycarbonate (PC) outdoor light is protected in any weather. With a CRI of over 90, colours have a natural appearance. It is quick and easy to establish a direct connection to a 220 volt supply. Please note, the MANA BASE WL PHASE must be combined with the matching MANA shade.



TECHNICAL DATA

Item no.	1006319
IP Code	IP65
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	68
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Ambient temperature	67 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	71
Number of luminaires at LS C16A	89
Level of inrush current	14 A
Duration of inrush current	8.5 µs
Lumen	1070/1100 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90

Light Source

	
--	---

Accessories

1008203	MANA 40 lampshade , round, H: 2.2 cm, white
1008205	MANA 40 lampshade , round, moon structure, H: 2.2 cm, gold
1004661	MANA , shade round 40 grey
1004660	MANA , shade round 40 beige
1008204	MANA 60 lampshade , round, h: 4.2 cm, white
1008202	MANA 60 lampshade , round, H: 4.2 cm, black
1004662	MANA , shade round 60 beige
1006318	MANA RUSTY , Lampshade round rust
1008201	MANA 40 lampshade , round, H: 2.2 cm, black
1008206	MANA 60 lampshade , round, moon structure, H: 4.2 cm, gold
1004663	MANA , shade round 60 grey
1006317	MANA RUSTY , Lampshade square rust

Service life	50000 h
Risk Group	1
Height	9 cm
Diameter	10 cm
Net weight	0.536 kg
Gross weight	0.608 kg
BIG WHITE Page	377