




RUSTY® PATHLIGHT70

LED outdoor floor stand, rust coloured, IP55, 3000 K

The direct radiating floor stands of the RUSTY series convince by their exceptional rust look. This is achieved by a special chemical treatment of the FeCSi steel used. This makes the luminaire a unique piece and an absolutely special feature wherever they are installed. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. Equipped with a powerful LED, the luminaire connects directly to a 230V mains voltage supply.

TECHNICAL DATA

Item no.	1006347
Number of different light outlets	1
IP Code	IP55
Impact resistance class	IK 06
Impact resistance	1 Joule
Primary nominal voltage	220-240V ~50/60 Hz
Safety class	I
Wattage	8.8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	470 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	rust
CRI	80
Service life	25000 h
Length	15 cm
Width	25 cm
Height	70 cm
Net weight	22.105 kg
Gross weight	23.563 kg
BIG WHITE Page	753

Light Source

954785	
--------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
229422	Earth spike , galvanised steel, 50 cm