




IN-LINE 22 48V TRACK

opal, DALI, spot, black / black, 7.3 W, 540 lm, 2700 K, CRI 90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 95° beam angle in various lumen and natural colour reproduction (CRI >90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



TECHNICAL DATA

Item no.	1006615
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48DC
Secondary power / voltage	350 mA
Safety class	III
Wattage	7.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Lumen	540 lm
Colour temperature	2700 Kelvin
Beam angle	95 °
Color	black/black
UGR ≤	28
Service life	50000 h
Risk Group	1
Length	22 cm
Width	2.2 cm

Light Source

2115946	
---------	---

Height	5.5 cm
Net weight	0.18 kg
Gross weight	0.215 kg
BIG WHITE Page	523