




IN-LINE 44 48V TRACK

opal, DALI, spot, white / white, 14 W, 1140 lm, 2700 K, CRI 90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 95° beam angle in various lumen and natural colour reproduction (CRI >90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



TECHNICAL DATA

Item no.	1006622
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	48DC
Secondary power / voltage	350 mA
Safety class	III
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Lumen	1140 lm
Colour temperature	2700 Kelvin
Beam angle	95 °
Color	white/white
UGR ≤	28
Service life	50000 h
Risk Group	1
Length	43.5 cm
Width	2.2 cm

Light Source

2115949		Height	2.5 cm
		Net weight	0.296 kg
		Gross weight	0.351 kg
		BIG WHITE Page	525