





IN-LINE 22 48V TRACK

Darklight Reflector, DALI, spot, white / white, 7.3 W, 610 lm, 3000 K, CRI 90, 35°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 35° beam angle in various lumen, adjustable lighting colour via a CCT switch (2700 K/3000 K/4000 K) and natural colour reproduction (CRI >90). As a result, the DARKLIGHT REFLECTOR creates an atmosphere that particularly showcases restaurants, bars and hotels in a new light. The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



TECHNICAL DATA

Item no.	1006630
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	48DC
Secondary power / voltage	350 mA
Safety class	III
Wattage	7.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Lumen	610 lm
Colour temperature	3000 Kelvin
Beam angle	35 °
Color	white/white
UGR ≤	16
Service life	50000 h
Risk Group	1
Length	22 cm
Width	2.2 cm

Light Source

2027084	
---------	---

Height	2.5 cm
Net weight	0.194 kg
Gross weight	0.228 kg
BIG WHITE Page	523