




NUMINOS® XS 48V TRACK

DALI, spot, black / black, 8.7W, 640lm, 2700K, CRI90, 55°

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



TECHNICAL DATA

Item no.	1006657
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Track,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48V
Secondary power / voltage	200 mA
Safety class	III
Wattage	8.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.5 W
Lumen	640 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	25

Light Source

798300	
--------	---

Accessories

1005614	NUMINOS® XS , frosted diffuser
1005612	NUMINOS® XS , diffuser
1005615	NUMINOS® XS , black diffuser
1005613	NUMINOS® XS , transparent diffuser

LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	5 cm
Net weight	0.178 kg
Gross weight	0.19 kg
BIG WHITE Page	469