




## NUMINOS® XS 48V TRACK

DALI, spot, white / white, 8.7W, 650lm, 2700K, CRI90, 40°

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



### TECHNICAL DATA

|                                   |                                |
|-----------------------------------|--------------------------------|
| Item no.                          | 1006664                        |
| Number of different light outlets | 1                              |
| Rotating or tilting               | rotary bar and tiltable        |
| IP Code                           | IP 20                          |
| Impact resistance class           | IK 02                          |
| Impact resistance                 | 0.2 Joule                      |
| Assembly details                  | Track,Track Ceiling,Track Wall |
| Dimmable                          | Yes                            |
| Dimming technology                | DALI 2                         |
| Primary nominal voltage           | 48V                            |
| Secondary power / voltage         | 200 mA                         |
| Safety class                      | III                            |
| Wattage                           | 8.7 W                          |
| Minimum ambient temperature       | -20 °C                         |
| Maximum ambient temperature       | 35 °C                          |
| Network rated standby power       | 0.5 W                          |
| Lumen                             | 650 lm                         |
| Colour temperature                | 2700 Kelvin                    |
| Beam angle                        | 40 °                           |
| Color                             | white                          |
| CRI                               | 90                             |
| UGR ≤                             | 22                             |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 798300 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                    |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser     |
| 1005612 | NUMINOS® XS , diffuser             |
| 1005615 | NUMINOS® XS , black diffuser       |
| 1005613 | NUMINOS® XS , transparent diffuser |

|                |          |
|----------------|----------|
| LXXBXX data    | L80B50   |
| Service life   | 50000 h  |
| Risk Group     | 1        |
| Height         | 8 cm     |
| Diameter       | 5 cm     |
| Net weight     | 0.178 kg |
| Gross weight   | 0.19 kg  |
| BIG WHITE Page | 469      |