




## NUMINOS® S 48V TRACK

DALI, spot, white / chrome, 16W, 1050lm, 3000K, CRI-90, 20°

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700-K/3000K/4000K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



## TECHNICAL DATA

|                                   |                                |
|-----------------------------------|--------------------------------|
| Item no.                          | 1006734                        |
| Number of different light outlets | 1                              |
| Rotating or tilting               | rotary bar and tiltable        |
| IP Code                           | IP 20                          |
| Impact resistance class           | IK 02                          |
| Impact resistance                 | 0.2 Joule                      |
| Assembly details                  | Track,Track Ceiling,Track Wall |
| Dimmable                          | Yes                            |
| Dimming technology                | DALI 2                         |
| Primary nominal voltage           | 48V                            |
| Secondary power / voltage         | 350 mA                         |
| Safety class                      | III                            |
| Wattage                           | 16 W                           |
| Minimum ambient temperature       | -20 °C                         |
| Maximum ambient temperature       | 35 °C                          |
| Network rated standby power       | 0.5 W                          |
| Lumen                             | 1050 lm                        |
| Colour temperature                | 3000 Kelvin                    |
| Beam angle                        | 20 °                           |
| Color                             | white                          |
| CRI                               | 90                             |
| UGR ≤                             | 19                             |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791815 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                  |
|---------|----------------------------------|
| 1004789 | NUMINOS® S , diffuser<br>Wabe    |
| 1004788 | NUMINOS® S , diffuser<br>Frosted |
| 1004787 | NUMINOS® S , diffuser<br>Prisma  |
| 1004786 | NUMINOS® S , diffuser<br>Ellipse |

|                |          |
|----------------|----------|
| LXXBXX data    | L80B50   |
| Service life   | 50000 h  |
| Risk Group     | 1        |
| Height         | 9 cm     |
| Diameter       | 6 cm     |
| Net weight     | 0.326 kg |
| Gross weight   | 0.349 kg |
| BIG WHITE Page | 469      |