




UNIVERSAL DOWN-LIGHT MOVE PHASE recessed light

IP20, pivoting, 5/8W, 2700/3000/4000/6500K, 38°, without cover

Discreet and universal: the UNIVERSAL DOWNLIGHT MOVE PHASE recessed light creates targeted lighting thanks to its narrow beam angle of 38 degrees. It can be swivelled to target specific areas that need illumination. A wide range of colour temperature options (2700/3000/4000/6000K) can be selected via the CCT switch before installation. Natural colour reproduction is achieved with a CRI of over 90. And the Quick Connector Box ensures a quick and easy installation. You can also use the separately available decorative ring, which comes in white, black, gold or chrome.



TECHNICAL DATA

Item no.	1007090
Rotating or tilting	tiltable
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/90 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Operating efficiency (LOR)	90%
Number of luminaires at LS B16A	60
Number of luminaires at LS C16A	150
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.003

Light Source

1370515	
---------	---

Accessories

1007191	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, round, gold matt
1007187	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, gold
1007094	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, gold
1007186	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, aluminium
1007091	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, black
1007093	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, aluminium
1007194	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, gold matt
1007185	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, white
1007092	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP20, pivoting, round, white
1007184	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, black

Lumen	560/610/680/640 lm
Colour temperature	2700/3000/4000/6500 Kelvin
Beam angle	38 °
Color	black
CRI	90
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Risk Group	0
Height	6.4 cm
Diameter	8.5 cm
Net weight	0.245 kg
Gross weight	0.293 kg
Shape of cut-out	round
Installation depth	7.3 cm
Installation diameter	6.8 cm
BIG WHITE Page	207