




NEW TRIA® 68

recessed ceiling light, 2700 K, 60°, IP 20, round, black

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700 K/3000 K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

Item no.	1007388
Rotating or tilting	tiltable
IP Code	IP20
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Lumen	705 lm
Colour temperature	2700 Kelvin
Beam angle	60 °
Color	black
CRI	90
Service life	50000 h
Risk Group	1

Light Source

869193		Height	4 cm
		Diameter	8.2 cm
		Net weight	0.206 kg
		Gross weight	0.247 kg
		Shape of cut-out	round
		Installation depth	4 cm
		Installation diameter	6.8 cm
		BIG WHITE Page	105