




## NOBLO® SPOT

3~ spot, round, 4000K, 6W, trailing-edge phase, 32°, white


The rotating and pivoting NOBLO® SPOT shines across the board: quickly and easily mounted on the three-phase high-voltage track system, the new generation impresses with an improved colour reproduction index CRI>90, a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. Added to this is the high-quality light that creates a particularly cosy atmosphere in living areas, hotels and restaurants. Ideal for modern lighting concepts, made of high-quality aluminium, quickly installed and available in colour temperatures of 2700K, 3000K and 4000K. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.



## TECHNICAL DATA

Item no.	1007649
Rotating or tilting	Rotary bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Track Ceiling,Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	160
Level of inrush current	3.5 A
Duration of inrush current	120 µs
Stroboscopic effect (SVM)	0.4
Lumen	760 lm
Colour temperature	4000 Kelvin
Beam angle	32 °
Color	white

## Light Source

1425147		CRI	90
		LXXBXX data	L80B10
		Service life	50000 h
		Risk Group	1
		Length	10.5 cm
		Height	12.4 cm
		Diameter	5 cm
		Net weight	0.25 kg
		Gross weight	0.268 kg
		BIG WHITE Page	547