




48V SYSTEM

Intrack LED driver, 48VDC, 200 W, DALI Wireless integrated Casambi to DALI module, terminal for 220-240VAC, cable storage room, white

This Casambi to DALI Intrack LED power supply provides a constant 48 VDC output voltage with a maximum output of 200 W. It has been specially developed for 48 V track lighting systems from SLV, where the 230 VAC power cable is connected directly to the terminals. Excess cable lengths can be stowed out of sight in a cable duct. It is available in black and white, making it ideal for modern lighting installations where the focus is on efficiency and visual appeal. In contrast to the standard version, this model has an integrated Casambi to DALI module that enables wireless control if DALI cables are missing. The lights are controlled via Bluetooth using your smart device or the Casambi app. Up to 64 lights can be controlled in 8 groups.



TECHNICAL DATA

Item no.	1008383
IP Code	IP20
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	48 mA
Safety class	II
Safety class	II
Ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	14
Level of inrush current	60 A
Duration of inrush current	250 µs
Color	white
Length	28 cm
Width	2.3 cm
Height	4.4 cm
Net weight	0.28 kg
Gross weight	0.3 kg