




CONCRETE

Pole 55, PHASE, Free-standing lamp, 2700 K, IP65, Grey

The CONCRETE bollard light makes a striking statement in outdoor areas with its durable concrete housing. The robust material is resistant to weather and, with its IP65 protection rating, is ideally suited for use in demanding environments, even near the coast. The downwardly directed, rotationally symmetrical light distribution of the luminaire effectively prevents light pollution and ensures the targeted illumination of paths, patios, or garden areas. The warm 2700 K light colour with a low proportion of blue creates a pleasant and inviting atmosphere. Thanks to its dimmability and an impressive service life of 50,000 hours, the CONCRETE bollard light offers maximum flexibility and longevity. The CONCRETE bollard light is available in two heights: 35 cm and 55 cm.



TECHNICAL DATA

Item no.	1008839
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	96
Number of luminaires at LS C16A	154
Level of inrush current	10 A
Duration of inrush current	400 µs
Temperature at glass (light emission)	60 °C
Lumen	600 lm
Colour temperature	2700 Kelvin

Light Source

2254624	
---------	---

Color	gray
CRI	80
Service life	50000 h
Risk Group	1
Height	54 cm
Diameter	19.2 cm
Net weight	14.85 kg
Gross weight	16.19 kg
BIG WHITE Page	727