




## TRACKSPOT V 3 Ph. 18W 940 50°

### White


Compatible with S-Track and Eutrac systems, the TRACKSPOT V 3-phase spotlight is the perfect choice for price-conscious commercial projects with demanding quality requirements. is the perfect choice for price-conscious commercial projects with moderate quality requirements. With an energy efficiency of over 120 lm/W, excellent colour rendering with CRI 90, and a high luminous flux of up to 4,000 lumens, the luminaire is ideal for applications where lighting quality and cost efficiency are crucial. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT V guarantees a long-term lighting solution. Available in different versions with 18W or 32W, beam angles of 36° or 50°, and in 3,000 K or 4,000 K, the TRACKSPOT V offers the right solution for every project. The black and white colour variants enable harmonious integration into different room concepts.



## TECHNICAL DATA

Item no.	1008850
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	300-1050 mA
Safety class	II
Wattage	13 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	20
Number of luminaires at LS C16A	32
Level of inrush current	48 A
Duration of inrush current	4 µs
Lumen	1800 / 5590 lm
Colour temperature	4000 Kelvin
Beam angle	50 °
Color	white
CRI	90
UGR ≤	25
Service life	50000 h

## Light Source

2194011	
---------	---

<b>Length</b>	10.5 cm
<b>Height</b>	14 cm
<b>Diameter</b>	10 cm
<b>Net weight</b>	0.72 kg
<b>Gross weight</b>	0.88 kg