




## TRACKSPOT C 3 Ph. 17W 940 36°

### White

The TRACKSPOT C 3-phase spotlight, which is compatible with S-Track and Eutrac systems, is the ideal choice for demanding commercial projects with a moderate budget, where high efficiency and the lowest possible energy consumption are the key points of focus. With an energy efficiency of over 145 lm/W, excellent colour rendering thanks to CRI 90, and a high luminous flux of up to 4,400 lumens, the luminaire offers a lighting solution that is perfect for small and large commercial areas. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT C also ensures long-term reliability and reduces maintenance costs. Available in different versions with 17W or 29W, beam angles of 36° or 50°, in 3,000 K and 4,000 K, the TRACKSPOT C comes in black and white versions. This flexibility enables harmonious integration into different room concepts.



## TECHNICAL DATA

Item no.	1008864
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	450-600 mA
Safety class	II
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	21
Number of luminaires at LS C16A	34
Level of inrush current	45 A
Duration of inrush current	400 µs
Lumen	2680 / 3500 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	25
Service life	50000 h

## Light Source

2194011	
---------	---

<b>Length</b>	10.5 cm
<b>Height</b>	14 cm
<b>Diameter</b>	10 cm
<b>Net weight</b>	0.72 kg
<b>Gross weight</b>	0.88 kg