




GRIP! S

Ceiling-mounted light, single, PHASE, 3000K, 11W, 29°, gold / black

GRIP! - the striking light family for sophisticated lighting design. With its distinctive knurled front ring and many new pendant, surface-mounted and recessed options, GRIP! now offers even more options for customised lighting concepts. The honeycomb louvre insert supplied as standard reduces glare and ensures optimum visual comfort. Different colours and designs blend harmoniously into living spaces, hotels or restaurants. High-quality technology with a CRI of 90, a lifetime of 50,000 hours and easy installation make GRIP! an all-round convincing choice.



TECHNICAL DATA

| | |
|---------------------------------|--------------------|
| Item no. | 1009043 |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 260 mA |
| Safety class | I |
| Wattage | 11 W |
| Minimum ambient temperature | 0 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 200 |
| Number of luminaires at LS C16A | 200 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Lumen | 650 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 29 ° |
| Color | gold/black |

Light Source

| | |
|---------|---|
| 2093886 |  |
|---------|---|

Accessories

| | |
|---------|-----------------------------------|
| 1008489 | GRIP! S , decorative ring, black |
| 1008488 | GRIP! S , decorative ring, white |
| 1008490 | GRIP! S , decorative ring, nickel |
| 1008491 | GRIP! S , decorative ring, gold |

| | |
|----------------|----------|
| CRI | 90 |
| UGR ≤ | 25 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 12.4 cm |
| Width | 10.1 cm |
| Height | 8.4 cm |
| Net weight | 0.256 kg |
| Gross weight | 0.366 kg |
| BIG WHITE Page | 147 |