


SIGHT PANEL

3~ spot, rectangular, 4000K, 38W, 70°, white

SIGHT PANEL - the high-output spot solution for 3-phase track mounting in shops, galleries or exhibition areas. With a 70° beam angle, CRI>90 and optional DALI control, it provides precise, high-quality light exactly where it is needed. The flexible swivel mechanism allows for precise alignment and the easy installation saves time - for perfect staging of any project.



TECHNICAL DATA

| | |
|---------------------------------|-------------------------------|
| Item no. | 1009149 |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 210/260/310/380 mA |
| Safety class | I |
| Wattage | 38 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 24 |
| Number of luminaires at LS C16A | 24 |
| Level of inrush current | 19 A |
| Duration of inrush current | 280 µs |
| Lumen | 6500 / 7950 / 9350 / 11350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 70 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| Service life | 50000 h |

Light Source

| | |
|---------|---|
| 2432904 |  |
|---------|---|

| | |
|-----------------------|---------|
| Length | 58 cm |
| Width | 19 cm |
| Height | 6.5 cm |
| Net weight | 2.03 kg |
| Gross weight | 2.39 kg |
| BIG WHITE Page | 640 |