


NUMINOS® XS

Recessed ceiling light, 4000 K, 40°, IP20, round, white

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009317
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1000 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	4.5 cm
Diameter	6.5 cm
Net weight	0.1 kg
Gross weight	0.2 kg

Light Source

2093754	
---------	---

Accessories

1005614	NUMINOS® XS , frosted diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1005613	NUMINOS® XS , transparent diffuser
1010126	NUMINOS® XS , reflector, copper
1010125	NUMINOS® XS , reflector, gold

Shape of cut-out	round
Installation depth	11 cm
Installation diameter	5.5 cm
BIG WHITE Page	25