


## NUMINOS® MOVE XS

Recessed ceiling light, 2700 K, 20°, IP20, round, black / white

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1009326
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	900 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black/white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.3 cm
Diameter	8 cm
Net weight	0.11 kg

## Light Source

2093755	
---------	---

### Accessories

1006136	Numinos® XS Reducing ring , round 160/70 mm white
1006135	Numinos® XS Reducing ring , round 160/70 mm black
1005614	NUMINOS® XS , frosted diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70 mm black
1006138	Numinos® XS Reducing ring , square 160/70 mm white
1005613	NUMINOS® XS , transparent diffuser
1010126	NUMINOS® XS , reflector, copper
1010125	NUMINOS® XS , reflector, gold

Gross weight	0.22 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm