




## NUMINOS® S

**Recessed ceiling light, 2700 K, 40°, IP20, round, black**

The NUMINOS light system from SLV combines technology, design and functionality like no other. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL S recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 6.7 watts, luminous flux of 1000 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

Item no.	1009436
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1000 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.2 cm
Diameter	8 cm
Net weight	0.13 kg
Gross weight	0.23 kg

## Light Source

2093739	
---------	---

## Accessories

1006136	Numinos® XS Reducing ring , round 160/70 mm white
1006135	Numinos® XS Reducing ring , round 160/70 mm black
1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honeycomb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1006137	Numinos® XS Reducing ring , square 160/70 mm black
1006138	Numinos® XS Reducing ring , square 160/70 mm white
1010680	NUMINOS® S , Prismatic diffuser
1010128	NUMINOS® S , reflector, copper
1010127	NUMINOS® S , reflector, gold

Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	27