


NUMINOS® MOVE S

Recessed ceiling light, 2700 K, 20°, IP20, round, black

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1009487 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 6.7 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 1000 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 6.35 cm |
| Diameter | 10 cm |
| Net weight | 0.188 kg |

Light Source

| | |
|---------|---|
| 2093739 |  |
|---------|---|

Accessories

| | |
|---------|---|
| 1010681 | NUMINOS® S , frosted diffuser |
| 1010682 | NUMINOS® S , Elliptical diffuser |
| 1006139 | Numinos® S Reducing ring , round 160/90 mm black |
| 1010679 | NUMINOS® S , Honeycomb diffuser |
| 1010695 | LED driver , 21W, 200 mA, DALI |
| 1010703 | LED driver , 23W, 200 mA, DALI |
| 1010699 | LED driver , 10W, 200 mA, PHASE |
| 1006140 | Numinos® S Reducing ring , round 160/90 mm white |
| 1006142 | Numinos® S Reducing ring , square 160/90 mm white |
| 1010680 | NUMINOS® S , Prismatic diffuser |
| 1006141 | Numinos® S Reducing ring , square 160/90 mm black |
| 1010128 | NUMINOS® S , reflector, copper |
| 1010127 | NUMINOS® S , reflector, gold |

| | |
|-----------------------|----------|
| Gross weight | 0.288 kg |
| Shape of cut-out | round |
| Installation depth | 8.5 cm |
| Installation diameter | 9 cm |
| BIG WHITE Page | 36 |