




NUMINOS® M

Recessed ceiling light, 2700 K, 20°, IP20, round, black

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1700 lumens, a colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009595
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

Light Source

2093870	
---------	---

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010683	NUMINOS® M , Honey-comb diffuser
1006139	Numinos® S Reducing ring , round 160/90 mm black
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prismatic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1006140	Numinos® S Reducing ring , round 160/90 mm white
1006142	Numinos® S Reducing ring , square 160/90 mm white
1006141	Numinos® S Reducing ring , square 160/90 mm black
1010129	NUMINOS® M , reflector, gold
1010130	NUMINOS® M , reflector, copper

Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm
BIG WHITE Page	28