


NUMINOS® M

Recessed ceiling light, 2700 K, 40°, IP20, round, black / white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The various downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1700 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009599
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black/white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

Light Source

2093870	
---------	---

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010683	NUMINOS® M , Honey-comb diffuser
1006139	Numinos® S Reducing ring , round 160/90 mm black
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prismatic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1006140	Numinos® S Reducing ring , round 160/90 mm white
1006142	Numinos® S Reducing ring , square 160/90 mm white
1006141	Numinos® S Reducing ring , square 160/90 mm black
1010129	NUMINOS® M , reflector, gold
1010130	NUMINOS® M , reflector, copper

Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm