


## MNUMINOS® S

Recessed ceiling light, 3000 K, 40°, IP20, round, white

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1800 lumens, a colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009626     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 350 mA      |
| Safety class                      | III         |
| Wattage                           | 12 W        |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 1800 lm     |
| Colour temperature                | 3000 Kelvin |
| Beam angle                        | 40 °        |
| Color                             | white       |
| CRI                               | 90          |
| UGR ≤                             | 19          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 6.8 cm      |
| Diameter                          | 10.5 cm     |
| Net weight                        | 0.22 kg     |
| Gross weight                      | 0.28 kg     |

## Light Source

|         |   |
|---------|---|
| 2093856 |  |
|---------|---|

## Accessories

|         |   |
|---------|---|
| 1010704 | LED driver , 23W, 350 mA, DALI                    |
| 1010700 | LED driver , 20W, 350 mA, PHASE                   |
| 1010683 | NUMINOS® M , Honey-comb diffuser                  |
| 1006139 | Numinos® S Reducing ring , round 160/90 mm black  |
| 1010686 | NUMINOS® M , Elliptical diffuser                  |
| 1010684 | NUMINOS® M , Prismatic diffuser                   |
| 1010696 | LED driver , 21W, 350 mA                          |
| 1010685 | NUMINOS® M , frosted diffuser                     |
| 1006140 | Numinos® S Reducing ring , round 160/90 mm white  |
| 1006142 | Numinos® S Reducing ring , square 160/90 mm white |
| 1006141 | Numinos® S Reducing ring , square 160/90 mm black |
| 1010129 | NUMINOS® M , reflector, gold                      |
| 1010130 | NUMINOS® M , reflector, copper                    |

|                       |        |
|-----------------------|--------|
| Shape of cut-out      | round  |
| Installation depth    | 7.5 cm |
| Installation diameter | 9 cm   |
| BIG WHITE Page        | 29     |