




NUMINOS® GIMBLE L

Recessed ceiling light, 4000 K, 20°, IP20, round, black / white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1009740 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 500 mA |
| Safety class | III |
| Wattage | 17 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 2700 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 20 ° |
| Color | black/white |
| CRI | 90 |
| UGR ≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 11.5 cm |
| Diameter | 16 cm |
| Net weight | 0.606 kg |

Light Source

| | |
|---------|---|
| 2093752 |  |
|---------|---|

Accessories

| | |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150 mm white |
| 1006149 | Numinos® L Reducing ring , square 240/150 mm black |
| 1010689 | NUMINOS® L , Frosted diffuser |
| 1010697 | LED driver , 21W, 500 mA |
| 1010687 | NUMINOS® L , Honeycomb diffuser |
| 1010701 | LED driver , 19 W, 500 mA, PHASE |
| 1010688 | NUMINOS® L , Prismatic diffuser |
| 1006150 | Numinos® L Reducing ring , square 240/150 mm white |
| 1006147 | Numinos® L Reducing ring , round 240/150 mm black |
| 1010690 | NUMINOS® L , Elliptical diffuser |
| 1010705 | LED driver , 36W, 500 mA, DALI |
| 1010132 | NUMINOS® L , reflector, copper |
| 1010131 | NUMINOS® L , reflector, gold |

| | |
|-----------------------|----------|
| Gross weight | 0.756 kg |
| Shape of cut-out | round |
| Installation depth | 11.5 cm |
| Installation diameter | 14.5 cm |